



O-Ring Sizes

KRS Part No.	AS-568 Part No.	Inner Dia	Tolerance	Cross Section	Tolerance
26-12	102	1.24	0.13	2.62	0.08
26-20	103	2.06	0.13	2.62	0.08
26-28	104	2.84	0.13	2.62	0.08
26-36	105	3.63	0.13	2.62	0.08
24-48	106	4.82	0.13	2.62	0.08
26-52	107	5.23	0.13	2.62	0.08
26-60	108	6.02	0.13	2.62	0.08
26-77	109	7.59	0.13	2.62	0.08
26-92	110	9.19	0.13	2.62	0.08
26-108	111	10.77	0.13	2.62	0.08
26-124	112	12.37	0.13	2.62	0.08
26-139	113	13.94	0.18	2.62	0.08
26-155	114	15.54	0.23	2.62	0.08
26-171	115	17.12	0.23	2.62	0.08
26-187	116	18.72	0.23	2.62	0.08
26-203	117	20.29	0.25	2.62	0.08
26-219	118	21.89	0.25	2.62	0.08
26-235	119	23.47	0.25	2.62	0.08
26-251	120	25.07	0.25	2.62	0.08
26-266	212	26.64	0.25	2.62	0.08
26-282	122	28.24	0.25	2.62	0.08
26-298	123	29.82	0.30	2.62	0.08
26-314	124	31.42	0.30	2.62	0.08
26-330	125	32.99	0.30	2.62	0.08
26-346	126	34.59	0.30	2.62	0.08
26-362	127	36.17	0.30	2.62	0.08
26-378	128	37.77	0.30	2.62	0.08
26-393	129	39.34	0.38	2.62	0.08
26-409	130	40.94	0.38	2.62	0.08
26-425	131	42.52	0.38	2.62	0.08
26-441	132	44.12	0.38	2.62	0.08
26-457	133	45.69	0.38	2.62	0.08
26-473	134	47.29	0.38	2.62	0.08
26-489	135	48.9	0.43	2.62	0.08
26-505	136	50.47	0.43	2.62	0.08
26-521	137	52.07	0.43	2.62	0.08
26-536	138	53.64	0.43	2.62	0.08
26-552	139	55.25	0.43	2.62	0.08
26-568	140	56.82	0.43	2.62	0.08
26.584	141	58.42	0.51	2.62	0.08
26-600	142	59.99	0.51	2.62	0.08
26-616	143	61.60	0.51	2.62	0.08
26-632	144	63.17	0.51	2.62	0.08
26-648	145	64.77	0.51	2.62	0.08
26-663	146	66.34	0.51	2.62	0.08
26-680	147	67.95	0.56	2.62	0.08
26-695	148	69.52	0.56	2.62	0.08
26-713	149	71.12	0.56	2.62	0.08
26-728	150	72.69	0.56	2.62	0.08
26-759	151	75.87	0.56	2.62	0.08

*** ALL DIMENSIONS ARE IN MM**