

O-Ring Sizes



KRS Part No.	AS-568 Part No.	Inner Dia	Tolerance	Cross Section	Tolerance
26-822	152	82.22	0.61	2.62	0.08
26-886	153	88.57	0.61	0.62	0.08
26-949	154	94.92	0.71	0.62	0.08
26-1013	155	101.27	0.71	0.62	0.08
26-1076	156	107.62	0.76	2.62	0.08
26-1140	157	113.97	0.76	2.62	0.08
26-1203	158	120.32	0.76	2.62	0.08
26-1267	159	126.67	0.89	2.62	0.08
26-1330	160	133.02	0.89	2.62	0.08
26-1394	161	139.37	0.89	2.62	0.08
26-1457	162	145.72	0.89	2.62	0.08
26-1521	163	152.07	0.89	2.62	0.08
26-1584	164	158.42	1.02	2.62	0.08
26-1647	165	164.77	1.02	2.62	0.08
26-1710	166	171.12	1.02	2.62	0.08
26-1775	167	177.47	1.02	2.62	0.08
26-1838	168	183.82	1.14	2.62	0.08
26-1901	169	190.17	1.14	2.62	0.08
26.1965	170	196.52	1.14	2.62	0.08
26.2028	171	202.87	1.14	2.62	0.08
26.2091	172	209.22	1.27	2.62	0.08
26-2156	173	215.57	1.27	2.62	0.08
26-2219	174	221.92	1.27	2.62	0.08
26-2283	175	228.27	1.27	2.62	0.08
26-2346	176	234.62	1.40	2.62	0.08
26-2409	177	240.97	1.40	2.62	0.08
26-2473	178	247.32	1.40	2.62	0.08
35-43	201	4.34	0.13	3.53	0.10
35-59	202	5.94	0.13	3.53	0.10
35-75	203	7.52	0.13	3.53	0.10
35-91	204	9.12	0.13	3.53	0.10
35-107	205	10.69	0.13	3.53	0.10
35-123	206	12.29	0.13	3.53	0.10
35-139	207	13.87	0.13	3.53	0.10
35-155	208	15.47	0.23	3.53	0.10
35-170	209	17.04	0.23	3.53	0.10
35-186	210	18.64	0.25	3.53	0.10
35.202	211	20.22	0.25	3.53	0.10
35-218	212	21.82	0.25	3.53	0.10
35-234	213	23.39	0.25	3.53	0.10
35-250	214	24.99	0.25	3.53	0.10
35-266	215	26.57	0.25	3.53	0.10
35-282	216	28.17	0.30	3.53	0.10
35-298	217	29.74	0.30	3.53	0.10
35-313	218	31.34	0.30	3.53	0.10
35-329	219	32.92	0.30	3.53	0.10
35-345	220	34.52	0.30	3.53	0.10
35-361	221	36.09	0.30	3.53	0.10
35-377	222	37.69	0.38	3.53	0.10
35-408	223	40.87	0.38	3.53	0.10

*** ALL DIMENSIONS ARE IN MM**