



O-Ring Sizes

KRS Part No.	AS-568 Part No.	Inner Dia	Tolerance	Cross Section	Tolerance
35-440	224	44.04	0.38	3.53	0.10
35-472	225	47.22	0.46	3.53	0.10
35-504	226	50.39	0.46	3.53	0.10
35-536	227	53.57	0.46	3.53	0.10
35-567	228	56.74	0.51	3.53	0.10
35-599	229	59.92	0.51	3.53	0.10
35-631	230	63.09	0.51	3.53	0.10
35-663	231	66.27	0.51	3.53	0.10
35-694	232	69.44	0.61	3.53	0.10
35-726	233	72.62	0.61	3.53	0.10
35-759	234	75.79	0.61	3.53	0.10
35-790	235	78.97	0.61	3.53	0.10
35-821	236	82.14	0.61	3.53	0.10
35-853	237	85.32	0.61	3.53	0.10
35-885	238	88.49	0.61	3.53	0.10
35-917	239	91.67	0.71	3.53	0.10
35-948	240	94.84	0.71	3.53	0.10
35-980	240	98.02	0.71	3.53	0.10
35-1012	242	101.19	0.71	3.53	0.10
35-1044	243	104.37	0.71	3.53	0.10
35-1075	244	107.54	0.76	3.53	0.10
35-1107	245	110.72	0.76	3.53	0.10
35-1139	246	113.89	0.76	3.53	0.10
35-1171	247	117.07	0.76	3.53	0.10
35-1202	248	120.24	0.76	3.53	0.10
35-1234	249	123.42	0.89	3.53	0.10
35-1266	250	126.59	0.89	3.53	0.10
35-1298	251	129.77	0.89	3.53	0.10
35-1329	252	132.94	0.89	3.53	0.10
35-1361	253	136.12	0.89	3.53	0.10
35-1393	254	139.29	0.89	3.53	0.10
35-1425	255	142.47	0.89	3.53	0.10
35-1456	256	145.64	0.89	3.53	0.10
35-1488	257	148.82	0.89	3.53	0.10
35-1520	258	151.99	0.89	3.53	0.10
35-1583	259	158.34	1.02	3.53	0.10
35-1647	260	164.69	1.02	3.53	0.10
35-1710	261	171.04	1.02	3.53	0.10
35-1774	262	177.39	1.02	3.53	0.10
35-1837	263	183.74	1.14	3.53	0.10
35-1901	264	190.09	1.14	3.53	0.10
35-1964	265	196.44	1.14	3.53	0.10
35-2028	266	202.79	1.14	3.53	0.10
35-2091	267	209.14	1.27	3.53	0.10
35-2155	268	215.49	1.27	3.53	0.10
35-2218	269	221.84	1.27	3.53	0.10
35-2282	270	228.19	1.27	3.53	0.10
35-2345	271	234.54	1.40	3.53	0.10
35-2409	272	240.89	1.40	3.53	0.10
35-2472	273	247.24	1.40	3.53	0.10

*** ALL DIMENSIONS ARE IN MM**