

O-Ring Sizes



KRS Part No.	AS-568 Part No.	Inner Dia	Tolerance	Cross Section	Tolerance
35-2536	274	253.59	1.40	3.53	0.10
35-2663	275	266.29	1.40	3.53	0.10
35-2790	276	278.99	1.65	3.53	0.10
35-2917	277	291.69	1.65	3.53	0.10
35-3044	278	304.39	1.65	3.53	0.10
35-3298	279	329.79	1.65	3.53	0.10
35-3552	280	355.19	1.65	3.53	0.10
35-3806	281	380.59	1.65	3.53	0.10
35-4052	282	405.26	1.91	3.53	0.10
35-4306	283	430.66	2.03	3.53	0.10
35-4561	284	456.06	2.16	3.53	0.10
53-105	309	10.46	0.13	5.33	0.13
53-121	310	12.07	0.13	5.33	0.13
53-136	311	13.64	0.18	5.33	0.13
53-152	312	15.24	0.23	5.33	0.13
53-168	313	16.81	0.23	5.33	0.13
53-184	314	18.42	0.25	5.33	0.13
53-200	315	19.99	0.25	5.33	0.13
53-216	316	21.59	0.25	5.33	0.13
53-232	317	23.16	0.25	5.33	0.13
53-250	318	24.77	0.25	5.33	0.13
53-264	319	26.34	0.25	5.33	0.13
53-280	320	27.94	0.30	5.33	0.13
53-295	321	29.51	0.30	5.33	0.13
53-315	322	31.12	0.30	5.33	0.13
53-327	323	32.69	0.30	5.33	0.13
53-343	324	34.29	0.30	5.33	0.13
53-375	325	37.47	0.38	5.33	0.13
53-406	326	40.64	0.38	5.33	0.13
53-438	327	43.82	0.38	5.33	0.13
53-470	328	46.99	0.38	5.33	0.13
53-502	329	50.17	0.46	5.33	0.13
53-533	330	53.34	0.46	5.33	0.13
53-565	331	56.52	0.46	5.33	0.13
53-597	332	59.69	0.46	5.33	0.13
53-629	333	62.87	0.51	5.33	0.13
53-660	334	66.04	0.51	5.33	0.13
53-692	335	69.22	0.51	5.33	0.13
53-724	336	72.39	0.51	5.33	0.13
53-756	337	75.57	0.61	5.33	0.13
53-787	338	78.74	0.61	5.33	0.13
53-819	339	81.92	0.61	5.33	0.13
53-851	340	85.09	0.61	5.33	0.13
53-883	341	88.27	0.61	5.33	0.13
53-914	342	91.44	0.71	5.33	0.13
53-946	343	94.62	0.71	5.33	0.13
53-978	344	97.79	0.71	5.33	0.13
53-1010	345	100.97	0.71	5.33	0.13
53-1041	346	104.14	0.71	5.33	0.13
53-1073	347	107.32	0.76	5.33	0.13

*** ALL DIMENSIONS ARE IN MM**